

Electro-Polished Pumps

Transfer pumps for ultra high-purity solvents and other non-corrosive liquids compatible with 316 Stainless Steel.

- 20RA Electro Polished 316 Stainless Steel wetted components
- PTFE Elastomers
- *1/2", 3/4" & 1" FNPT liquid port sizes standard.
 Also available sanitary welded.
- · Leak-free, registered fit, mating surfaces
- Patented, self-lubricating air valve never needs internal or external lubrication
- Non-stalling air valve which includes a noncentering, spring assisted shuttle, ensuring a positive shift every time
- "Short Stroke" reduces diaphragm flex and extends life
- Maximum flow rate up to 35 gallons/minute
- Field-proven design
- Maintenance friendly
- Electro polished pulsation dampeners also available
- Custom air motor control options available





Applications

Acetone

Isopropyl Alcohol

Trichloroethylene

Methyl Ethyl Ketone

N-Methylpyrrolidone

And Many More...



Toll Free: 800-990-7867 www.yamadapump.com









Electro-Polished Pumps

SPECIFICATIONS	NDP-15BST-EP-20RA	NDP-20BST-EP-20RA	NDP-25BST-EP-20RA
Discharge Volume/Cycle	0.031 gal. (119 cc)	0.10 gal. (378 cc)	0.17 gal (654 cc)
Maximum Cycles/Minute	400	195	210
Port Dimensions:			
Liquid inlet & discharge	FNPT 1/2"	FNPT 3/4"	FNPT 1"
Air Inlet	FNPT 1/4"	FNPT 1/4"	FNPT 3/8"
Air Exhaust	FNPT 3/8"	FNPT 3/4"	FNPT 3/4"
Net Weight	14.5 lbs. (6.6 kg.)	33.1 lbs. (15 kg.)	50.7 lbs. (25 kg.)
Air Supply Pressure	All models: 20 to 100 PSI		
Maximum Liquid Temperature	All models: 212° F		





[Feet] [Meters] 300 80 250 70 100 PS/ 40 40 45 PS/ 100 20 30 45 PS/ 100 20 30 40 [Gal/Min] WATER DISCHARGE Data based on 1-ft. flooded suction, ambient water.

3. One piece capped Center Disk
4. Aluminum Air Motor with NO
PAINT

Optional Swagelok®, VCR®, Sanita
Optional clean room flush & baggir

PTFE Diaphragms

Note: All EP Series Pumps include:

20RA Electro Polished 316 Stainless Steel housings **Additional Options:**

Other diaphragm materials

PTFE coated air motor

For expanded technical information, please call Yamada or visit our website at yamadapump.com.

Optional Swagelok®, VCR®, Sanitary Clamp, Tube or ANSI Flange Connections. Optional clean room flush & bagging available.

Swagelok® & VCR® are trademarks of the Swagelok Companies.

Label:



www.yamadapump.com

Toll Free: 800-990-7867



