

## PLUS+1™ OX012-010 Expansion Module

### Mobile Machine Management

The OX012-010 output expansion module is an element of the flexible, powerful and expandable PLUS+1 family of mobile machine management products. Expansion modules provide cost-effective additional I/O to mobile machine control systems.

### Product Highlights

Output expansion modules are associated with a PLUS+1 controller. PLUS+1 GUIDE (Graphical User Integrated Development Environment) applications running in the controller write outputs to expansion module pins as if the pins are physically located on the controller. Pin properties are configured in the controller's GUIDE application.

PLUS+1 compliance eliminates need for the system designer to write CAN transmit and receive messages in both the controller and associated expansion modules.

### Application Development

Users configure expansion modules using PLUS+1 GUIDE. This Microsoft® Windows®-based development environment features a user-friendly, field proven, icon-based graphical programming tool, application downloader, and service/diagnostic tool.

Local Address:



  
COMPLIANT


*OX012-010 Expansion Module*

### Features


- 12 pin Deutsch® DTM connector
- 6 outputs
  - (6) universal (PWMOUT/DOUT/PVGOUT) that are user-defined as either:
    - Digital:* (3 A), configurable as a source or sink;
    - PWM:* (30 to 4000 Hz) configurable as open or closed loop with current control;
    - Analog voltage:* open loop PWM at 4000 Hz.
  - Any PWMOUT/DOUT/PVGOUT can be used to provide reference power to one PVG valve.
- 9 to 36 Vdc power supply, monitored internally
- 1 CAN 2.0B port
- 3 mounting alternatives: stack, end, or side
- CE compliant

## OX012-010 Dimensions and Pin Assignments

mm [in]



## 12 Pin Connector



Pin	Controller function
C1-P1	Power ground -
C1-P2	Power supply +
C1-P3	CAN +
C1-P4	CAN -
C1-P5	CAN shield
C1-P6	PWMOUT/DOU/PVGOUT
C1-P7	PWMOUT/DOU/PVGOUT
C1-P8	PWMOUT/DOU/PVGOUT
C1-P9	PWMOUT/DOU/PVGOUT
C1-P10	PWMOUT/DOU/PVGOUT
C1-P11	PWMOUT/DOU/PVGOUT
C1-P12	Power supply +

Use care when wiring mating connector.  
Above pinouts are for device pins.

### ⚠ Caution

PCB damage may occur. All device power supply + pins must be connected to battery +.

### ⚠ Caution

This device is not field serviceable. Opening the device housing will void the warranty.

## Specifications

Supply voltage	9 to 36 Vdc
Operating temperature (ambient)	-40°C to 70°C [-40°F to 158°F]
Storage temperature	-40°C to 85°C [-40°F to 185°F]
Programming temperature	0°C to 70°C [32°F to 158°F]
IP rating (with mating connector attached)	IP 67
EMI/ RFI rating	100 V/m
Weight	0.34 kg [0.75 lb]
Vibration	IEC 60068-2-64
Shock	IEC 60068-2-27 test Ea
Maximum current, sourcing	16 A
Maximum current, sinking	8 A

## Ordering Information

<b>OX012-010</b>	10100996	
<b>Related product</b>	<b>Sauer-Danfoss material number</b>	
CG150 CAN/USB Gateway	10104136	
Deutsch® mating connector bag assembly	10102025 (16 to 20 AWG)	10100944 (20 to 24 AWG)
PLUS+1 GUIDE single user license	10101000	

Comprehensive technical information: *PLUS+1 Controller Family Technical Information*, **520L0719**;  
*PLUS+1 Compliant OX012-010 Function Block User Manual*, **11063396**  
Sauer-Danfoss product literature on line at: [www.sauer-danfoss.com](http://www.sauer-danfoss.com)