

Outlet pressure (bar)	Average outlet flow (l/min)	Inlet pressure (bar)	Inlet flow (l/min)	Connection	Weight (kg)	Ratio	Model: Steel	Model: Stainless steel
24-800	0.3-0.5	20-200	2.0-8.0	Tube	0.7	1.2-7.5	HC1	HC1W
24-800	0.3-2.5	20-200	2.0-15.0	Tube	1.0	1.2-20.0	HC2	HC2W
24-800	0.7-11.0	20-200	2.0-15.0	Tube	3.8	1.2-20.0	HC2D	
20-800	2.0-3.0	20-200	2.0-15.0	Tube	4.15	1.0-10.1	HC2D2	HC2D2W
24-800	0.3-1.0	-	-	Tube	2.1	1.2-13.0	HC2P	
24-500	0.3-2.5	20-200	2.0-15.0	Manifold NG6/DO3	2.5	1.2-20.0	HC3	
24-500	0.3-2.5	20-200	2.0-15.0	Manifold NG6/DO3	4.0	1.2-20.0	HC3 - C	
24-500	0.3-2.5	20-200	2.0-15.0	Manifold	1.75	1.2-20.0	HC3 - D	
24-500	0.3-2.5	20-200	2.0-15.0	Manifold	4.3	1.2-20.0	HC3 - F	
24-500	0.3-2.5	20-200	2.0-15.0	Manifold NG6/DO3	3.3	1.2-20.0	HC3 - H	
24-500	0.3-2.5	20-200	2.0-15.0	Manifold NG6/DO3	3.5	1.2-20.0	HC3 - I	
26-800	1.5-7.0	20-200	2.0-35.0	Tube	3.7	1.3-9.8	HC4	HC4W
24-800	0.3-2.5	20-200	2.0-15.0	Tube	3.0	1.2-20.0	HC5	
26-800	2.5-15.0	20-200	5.0-70.0	Tube	9.5	1.3-8.2	HC6	
24-800	11.2-56.0	20-200	5.0-70.0	Tube	20.0	1.2-8.2	HC6D	HC6DW
20-800	6.0-41.0	20-200	5.0-70.0	Tube	22.0	1.0-10.1	HC6D2	HC6D2W
100-2000	0.3-1.6	20-200	2.0-14.0	Tube	1.5	5.0-20.0	HC7	HC7W
100-2000	0.3-1.6	20-200	2.0-14.0	Tube	5.0	5.0-20.0	HC8	
220-5000	0.3-1.8	20-200	5.0-20.0	Tube	9.9	8.2-25.0	HC9	
							HC9D2	HC9D2W